

...the future



### PORTABLE RECHARGEABLE FLOOD LIGHT- 30W

## SECTION 1: GENERAL DESCRIPTION (FIXTURE AND DRIVER)

| Model Number:<br>Time:<br>Hue:<br>Voltage:   | VOL-FL-030-CV<br>2HRS<br>C/W<br>85-265V        | V-2HR                            |                                       |
|--|--|----------------------------------|---------------------------------------|
| Power:<br>Diffuser Type:<br>Base Material:<br>Light Output:<br>Beam Angle:<br>Correlated Colour Temperate<br>(CCT): Fixture Lifespan:<br>IP Rating:<br>Dimensions:<br>Weight:<br>Charging Time:<br>Run Time: | 65<br>226 mm x 331<br>1.2 kg<br>3-4 hours      | 0+ years at 12 ho<br>mm x 182 mm |                                       |
| KUTTIME.   | Classes<br>1st Class<br>2nd Class<br>3rd Class | Power (W)<br>3.5<br>15<br>30     | Time of Use (Hours)<br>>2<br>>6<br>>8 |

- 1st class : weak light , can satisfy reading , catering and other etc. environment which light brightness requirement is low
- 2nd class : working light , can satisfy the low light brightness demand.
- 3rd class : high bright, can satisfy the high brightness demand

## **SECTION 2: CERTIFICATIONS MET**

- 1) UL Listing : Underwriters Laboratory testing for dependable reliability and lifespan of fixture.
- 2) RoHS Certification: Restriction of Hazardous Substances- Ensuring no toxic chemicals or materials are used in the manufacture.
- 3) CE Certification: Conformity European, Ensuring that this product can be within the strictest standards of Europe.

## SECTION 3: LIGHT SOURCE DESCRIPTION (LED CHIP)

| LED Shape:      | COB     |
|-----------------|---------|
| Number of LEDS: | 1       |
| LED TYPE:       | EPISTAR |

# SECTION 4: COMPARABLE OLDER LIGHT SOURCE

| 150W Halogen Work Light                     | 30W Portable Flood Light               |  |
|---|--|--|
| 150 Watts Power                             | 30 Watts Power                         |  |
| 8,000 Hour Lifespan                         | 50,000 Hour Lifespan                   |  |
| Carries no warranty                         | Carries 1 year warranty                |  |
| Contains deadly mercury gas                 | RoHS certified for no toxic components |  |
| Does not function well in cold environments | Works perfectly down to -20°C          |  |